



**Notified Body 1020**

# CERTIFICATE OF CONFORMITY OF THE FACTORY PRODUCTION CONTROL

**No. 1020 – CPR - 030055958**

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product:

## ALMEVA Triple DW25

**Three-layer chimney system with steel flue liner, 25 mm insulation  
 and a steel outer wall element with or without surface treatment**

type:

without surface treatment and a ventilated 50 mm wide gap in the ceiling:			with surface treatment and a ventilated 100 mm wide gap in the ceiling:		
<b>ALMEVA Triple DW25</b>			<b>ALMEVA Triple DW25</b>		
EN 1856-1	T600 N1 W V2 L50050 G50	(Ø 80-200 mm)	EN 1856-1	T600 N1 W V2 L50050 G100	(Ø 80-200 mm)
EN 1856-1	T600 N1 W V2 L50060 G50	(Ø 250-300 mm)	EN 1856-1	T600 N1 W V2 L50060 G100	(Ø 250-300 mm)
EN 1856-1	T600 N1 W V2 L50060 G75	(Ø 350-450 mm)	EN 1856-1	T600 N1 W V2 L50060 G150	(Ø 350-450 mm)
EN 1856-1	T600 N1 W V2 L50060 G100	(Ø 500-550 mm)	EN 1856-1	T600 N1 W V2 L50060 G200	(Ø 500-550 mm)
EN 1856-1	T600 N1 W V2 L50080 G100	(Ø 600 mm)	EN 1856-1	T600 N1 W V2 L50080 G200	(Ø 600 mm)
Three-layer chimney system with or without surface treatment and an insulated gap through the ceiling:					
<b>ALMEVA Triple DW25</b>					
EN 1856-1	T450 N1 W V2 L50050 G100	(Ø 80-200 mm)			
EN 1856-1	T450 N1 W V2 L50060 G100	(Ø 250-300 mm)			
EN 1856-1	T450 N1 W V2 L50060 G150	(Ø 350-450 mm)			
EN 1856-1	T450 N1 W V2 L50060 G200	(Ø 500-550 mm)			
EN 1856-1	T450 N1 W V2 L50080 G200	(Ø 600 mm)			
Three-layer chimney system with or without surface treatment and an insulated gap through the ceiling (silicone gasket):					
<b>ALMEVA Triple DW25</b>					
EN 1856-1	T200 P1 W V2 L50050 O50	(Ø 80-200 mm)			
EN 1856-1	T200 P1 W V2 L50060 O50	(Ø 250-300 mm)			
EN 1856-1	T200 P1 W V2 L50060 O75	(Ø 350-450 mm)			
EN 1856-1	T200 P1 W V2 L50060 O100	(Ø 500-550 mm)			
EN 1856-1	T200 P1 W V2 L50080 O100	(Ø 600 mm)			
Three-layer chimney system with or without surface treatment and an insulated gap through the ceiling (EPDM gasket):					
<b>ALMEVA Triple DW25</b>					
EN 1856-1	T120 P1 W V2 L50050 O50	(Ø 80-200 mm)			
EN 1856-1	T120 P1 W V2 L50060 O50	(Ø 250-300 mm)			
EN 1856-1	T120 P1 W V2 L50060 O75	(Ø 350-450 mm)			
EN 1856-1	T120 P1 W V2 L50060 O100	(Ø 500-550 mm)			
EN 1856-1	T120 P1 W V2 L50080 O100	(Ø 600 mm)			

placed on the market under the name or trade mark of

**Almeva East Europe s.r.o.**

664 43 Želešice, Družstevní 501, IČO: 283 03 156, CZ

and produced in the manufacturing plant

**Almeva East Europe s.r.o., 664 43 Želešice, Družstevní 501**


This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

**EN 1856-1:2009**

under system 2+ are applied and that

**the factory production control is assessed to be in conformity with the applicable requirements.**

This certificate was first issued on **November 23, 2017** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.



**Ing. Alexander Trinner**  
 Deputy manager of the Notified Body 1020

Plzeň, August 23, 2019

The stamp of the Notified Body 1020